

# Draka UC<sup>Connect</sup> Patch-Cords

Flexible Category 6a cables with RJ45 connectors for specific channel performance



## UC<sup>Connect</sup> System Patch-Cords

- Flexible stranded bare copper conductor patch cable
- 3p Component Complaint
- Part of the 3p Maintenance Programme.
- Flexible solid bar copper conductor CP-cable
- Utilises Cat7 patch cable to improve performance.
- 2xRJ45 connector (TIA568-B coding)
- Different jacketing options
- Different colour options (grey, blue, aqua, yellow, orange, red, green, black)
- DualBoot molded strain relief
- Latch protector

## Specification



<b>Product Family</b>	<b>Related Cable Description</b>
UC <sup>Connect</sup> 500 Class Ea Channel, screened	Cat.7 S/FTP 27/7 AWG 4P patch cable LSHF
<b>Performance</b>	
Flame resistance - PVC	IEC 60332-1
Flame resistance - LSHF	IEC 60332-1, IEC 60754-2, IEC 61034
Standards	EN 50173, ISO/IEC 11801 Amendment 2, IEC 60603-7
Length	1m, 2m, 3m, & 5m other lengths upon request

## Draka UC<sup>Connect</sup> Patch-Cords

Flexible Category 6a cables with RJ45 connectors for specific channel performance

### Technical Data

Material code	Description Code	Size	Weight	Items per packaging unit
YPCBP00170	UC C500 PC SF GY L 00100	LLLLL: Length option; length in cm (example: 00200 → 2,0m)		Packaging option (1 = 1 per bag, 2 = 5 per bag, 3 = 10 per bag)
YPCBP00171	UC C500 PC SF GY L 00200			
YPCBP00172	UC C500 PC SF GY L 00300			
YPCBP00173	UC C500 PC SF GY L 00500			
	CM – length in centimeters			
	Standard colours acc. to table			
	Packaging option to be identified with order information			
<b>Related Products</b>				
	<b>Marking clips</b>			
YMCBP00183	UC CACC PC Marking Clip blue 50pc			50 pieces
YMCBP00184	UC CACC PC Marking Clip yellow 50pc			50 pieces
YMCBP00185	UC CACC PC Marking Clip green 50pc			50 pieces
YMCBP00186	UC CACC PC Marking Clip black 50pc			50 pieces
YMCBP00187	UC CACC PC Marking Clip red 50pc			50 pieces

© PRYSMIAN GROUP 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.